

# E-ACCESS

## Bluetooth Access Control Proximity Readers/Keypads



**Easiprox<sup>+</sup>**

**Access Control Proximity Reader**

4 1/2" x 3 1/8" x 11/16"  
(114 x 80 x 18 mm)  
Navy blue finish



**Easiprox<sup>+</sup> Slim**

**Access Control Proximity Reader**

3 7/16" x 1 3/4" x 15/16"  
(88 x 44 x 23 mm)  
Black finish



**E1196**

**Access Control Reader**

4 1/2" x 2 3/4" x 1 3/16"  
(114 x 69.5 x 30 mm)  
Black/White finish



**DG-360<sup>+</sup>**

**Access Control Proximity Reader**

3 3/8" x 3 3/8" x 13/16"  
(86 x 86 x 20 mm)  
Black finish

*MOSFET Relay Included  
(for reduced electromagnetic  
interference)*



**DG-160<sup>+</sup>**

**Access Control Proximity Reader/Keypad**

6" x 1 3/4" x 15/16"  
(152 x 45 x 23 mm)  
Chrome finish  
Backlit Keypad



**DG-800<sup>+</sup>**

**Access Control Proximity Reader/Keypad**

4 13/16" x 3 1/8" x 15/16"  
(123 x 79 x 23mm)  
Chrome/Gold finish  
Backlit Keypad &  
Weatherized Housing

### Standard Features

- Allows smartphone-operated access
- Bluetooth operating range up to 50 meters
- Adjustable Auto proximity range for convenient access
- E-Access app available for easy access control and user management
- LED and built-buzzer indicate status



GIANNI INDUSTRIES, INC.

Tel: +886-2-2267-7986 Fax: +886-2-2267-9876  
www.gianni.com.tw inquiry1@gianni.com.tw

## Bluetooth Access Control Proximity Readers/Keypads

Model	E1196	Easiprox <sup>+</sup> Easiprox <sup>+</sup> Slim	DG-800 <sup>+</sup> DG-160 <sup>+</sup>	DG-360 <sup>+</sup>
<b>Technical Data and Functions</b>				
<b>Voltage (VDC)</b>	12 to 24	12	12VDC / 24 VDC	12 to 24
<b>Bluetooth Module</b>	BLE 4.0	BLE 4.2	BLE 4.2	BLE 4.2
<b>Administrator/Users</b>	1/196	1/200	1/200	1/200
<b>Access Modes</b>	Smartphone	Smartphone Prox card	Smartphone Prox card Keypad PIN code	Smartphone Prox card
<b>RFID Prox Card Read Range</b>	-	5 cm	3.5 cm	3 cm
<b>Interface</b>	REX & Door sensor input	REX & Door sensor input, Alarm output	REX & Door sensor input, Alarm output	REX & Door sensor input, Alarm output
<b>Tamper Alarm</b>	-	●	●	●
<b>Door Held Open Alarm (Built-in 85 dB buzzer)</b>	●	●	●	-
<b>Wrong Code Lockout</b>	-	-	●	-
<b>Anti-tailgate Function</b>	●	-	-	●
<b>E-Access App Functions</b>				
<b>Lock Action</b>	Keep unlocked/locked status or set relock time	Keep unlocked / locked status or set relock time	Keep unlocked/locked status or set relock time	Keep unlocked/locked status or set relock time
<b>User Management</b>	Grant or disable user access and manage user data	Add/Delete/View user data, grant user access for specific dates or time periods and change user passcode	Add/Delete/View user data, grant user access for specific dates or time periods and change user passcode	Add/Delete/View user data, grant user access for specific dates or time periods and change user passcode
<b>Audit Trail Events</b>	-	1000	1000	1000
<b>Backup/Restore Data</b>	●	●	●	●

Note:

1. RFID prox card: 125KHz frequency, EM or EM compatible card
2. Passcode/Keypad PIN code length: 4 to 8 digits

### Warranty

The product is warranted against defects in material and workmanship while used in normal service for a period of 1 year from the date of sale to the original client. The GEM policy is one of continual development and improvement; therefore GEM reserves the right to change specifications without notice.

